

Oxford



Features

- Frosted (UV stabilised polycarbonate) or clear polycarbonate bowl
- Wide range of colour temperatures
- Three light engine options
- Low whole life cost
- Fully programmable driver to operate with any CMS



Unit F1, Grafton Way
West Ham Industrial Estate
Basingstoke
RG22 6HY

Contact us
01256 308467
info@acrosfire.co

acrosfire.co

Oxford



CLASS I | IP65 | IK10

The Oxford is a versatile and timeless post top luminaire suitable for a range of applications, including housing developments and car parks. Typically installed on 6-8m columns. Available in wattages from 8-80W.



A 370 mm

B 930 mm

Wgt. 7.9 kg

PSA 0.14m²


FEATURES

- 2700K, 3000K or 4000K
- Lumen packages up to 10,000 Lumens
- Lightweight Aluminium body with high-pressure die-cast base and canopy
- Polyester powder coated and 1000 salt spray tested to survive the harshest of environments
- Optic bowl rated to IK10 and IP66 (gear compartment up to IP65)
- Integral surge protection
- L90 lifetime: 100,000 hours


BENEFITS

- Save up to 75% on traditional HID installations
- Vandal-resistant


PHOTOMETRY




ME




T3



T2



SCL



SYM AREA WD



Unit F1, Grafton Way
West Ham Industrial Estate
Basingstoke
RG22 6HY

Contact us
acrosfire.co
01256308467
info@acrosfire.co