

# Beme Bollard

Cost-effective pathway illumination for car parks, walkways, and footpath applications.

- Vandal-resistant IK10 design in a choice of four diameters and four mounting heights
- Illuminated, non-illuminated, and EV-charger options
- High-performance optics
- Asymmetric and symmetric lighting distributions
- 2200K, 2500K, 2700K, or 4000K
- Smart City ready (fully programmable driver option)

## Applications



Residential



Campus



Car Parks



Footpaths



Parks



Rail





### Bollard Specification

- Vandal resistant stainless steel illuminated bollard
- Asymmetric, symmetric and 180° lighting distributions

### Colour Temperature

- 2200K, 2500K, 2700K, or 4000K

### Electrical Specification

- Output Power (Watts) 20
- Electrical Class: Class 1

### Certification

- CE, UKCA

### Mounting

- Root mounted
- Flange

### Materials

- Stainless steel body: Grade 304 or 316L

### Options

- Also available in non-illuminated and ev-charger
- Diameters: 114mm, 168mm, 220mm, 275mm
- Mounting heights: 600mm, 750mm, 900mm, 1150mm
- Anti-graffiti finish
- Backshield

### Lumen Range (Lumens)

- 500-2000

### Control

- 1-10V pre-programmed dimming
- Pre-programmable driver option
- 3 hour emergency
- PIR option

### Finish

- Satin brushed stainless steel
- Polyester powder coat

### Colour

- Any standard RAL

### Operating Temperature

- From -20°C to 50°C

### Warranty

- 10 years

### Durability

- IP66 Ingress Protection
- IK10 Impact Resistance