

Loma Bollard

Cost-effective pathway illumination for car parks, walkways, and footpath applications.

- Vandal-resistant IK10 design in a choice of four diameters and four mounting heights
- Illuminated, non-illuminated, and EV-charger options
- High-performance optics
- Asymmetric and symmetric lighting distributions
- 2200K, 2500K, 2700K, or 4000K
- Smart City ready (fully programmable driver option)

Applications



Residential



Campus



Car Parks



Footpaths



Parks



Rail





Bollard Specification

- Vandal resistant stainless steel illuminated bollard
- Asymmetric and symmetric lighting distributions

Colour Temperature

- 2200K, 2500K, 2700K, or 4000K

Electrical Specification

- Output Power (Watts) 20
- Electrical Class: Class 1

Certification

- CE, UKCA

Mounting

- Root mounted
- Flange

Materials

- Stainless steel body: Grade 304 or 316L

Options

- Also available in non-illuminated and ev-charger
- Diameters: 114mm, 168mm, 220mm, 275mm
- Mounting heights: 600mm, 750mm, 900mm, 1150mm
- Anti-graffiti finish

Lumen Range (Lumens)

- 500-2000

Control

- 1-10V pre-programmed dimming
- Pre-programmable driver option
- 3 hour emergency
- PIR option

Finish

- Satin brushed stainless steel
- Polyester powder coat

Colour

- Any standard RAL

Operating Temperature

- From -20°C to 50°C

Warranty

- 10 years

Durability

- IP66 Ingress Protection
- IK10 Impact Resistance